

Industrial Computer ATX Series



1KW/1.2KW Multiple Output Active PFC Data Sheet

For the latest revision, please visit power.liteon.com

Description

This is a high-power factor (PF), multiple-output AC to DC switching mode power supply unit which can provide up to 1,000 / 1,200 watts continuous with forced cooling by a smart FSC (fan speed control) circuitry. There is a built-in auxiliary converter (5VSB) for energy saving purpose. It complies with 80+platinum as well as worldwide safety and EMC regulations (refer to details below). It is suitable for various industrial PC applications.

Features

- * Full AC input voltage range design.
- * High power factor and less fictitious power.
- * Withstand 300Vac surge voltage for 5 seconds.
- * Full Protections: Short-circuit/ Over-voltage/ Over-current/ Over temperature.
- * INTEL® standard ATX form factor.
- * Meet 80+platinum and support 200% peak power.
- * IEC/EN 62368-1 design compliance.
- * Up to 5000 meters operating altitude (note#4)
- * High efficiency and high reliability.
- * REM_ON/OFF and PWR_OK signal



Electrical Specification

Model Name	HS-5102-12/HS-5122-12				
Output					
Rated power	1KW/1.2KW				
Rated voltage	12V	5V	3.3V	-12V	5Vsb
Rated current	83A/100A	20A	20A	0.3A	3A
Ripple & Noise(max.) (note #2)	120mV	50mV	50mV	120mV	50mV
Line & load regulation	±5%	±5%	±5%	±10%	±5%
Hold-up time(typ.) (note #5)	16ms				
Timing: AC ON delay / rising (max.)	2 sec / 20ms				
Input					
Rated voltage range	100~240Vac				
Operated voltage range	90~264Vac, 300Vac for 5 sec				

Current range (max.)	14A/100Vac, 6A/200Vac for 1KW; 15A/100Vac, 7A/200Vac for 1.2KW
Inrush current	No component damaged ($<I^2 \cdot t$).
Frequency range	50-60Hz
Leakage current (max.)	3.5mA at 240Vac
Efficiency (min.)	90% - 92% - 89% (at 20% - 50% - 100% of rated loading)
Standby power saving (min.)	Pin<1.2W at 5Vsb/0.12A Pin<0.5W at 5Vsb/12mA
Protection Function	
Over voltage (max.)	140% of rated voltage, latch-off protection (for +12V/+5V/+3.3V)
Over current (max.)	Latch-off protection (for +12V/+5V/+3.3V)
Short circuit at O/P	Latch-off protection (for +12V/+5V/+3.3V)
Over temperature	Latch-off protection
Others	
MTBF (min.) (note#3)	700K hours @ rated load
Environment	
Temperature (note#5)	(operating) 0~50°C / (storage) -40~85°C
Humidity	(operating) 10~90% RH non-condensing / (storage) 5~95% RH
Altitude (max.)	5000 meters
Mechanical	
Dimension	150(L)*160(W)*86mm(H)
Vibration	10~500 Hz, 5G 20min./1cycle per axis for all axes (X, Y, Z)
Weight (typ.)	1750g (excluding output cable)
Safety	
Standard	IEC/EN 60950-1, K60950-1, IEC/EN 62368-1, CNS14336-1
Withstand voltage	Input-Output: 4242VDC / Input-FG: 2150VDC
Isolation resistance(min.)	Input-Output: 100Mohm @ 500VDC, 25°C, 70%RH
EMC	
EN55032 (CISPR32)	Conducted EMI: class B / Radiated EMI: class B
FCC	Conducted EMI: class B / Radiated EMI: class B
EN61000-3-2	Harmonic distortion: not applicable
EN61000-4-2	ESD: ±8KV contact discharge / ±15KV contact discharge
EN61000-4-3	Radiated RF immunity: 3V/m
EN61000-4-4	EFT: ±1KV (AC port)
EN61000-4-5	Surge: ±1KV DM / ±2KV CM
EN61000-4-6	Conducted RF immunity: 3V/m
EN61000-4-8	Magnetic field immunity: 3A/m
EN61000-4-11	Voltage dip immunity

Notes

- #1: All specification defined at 230Vac/50Hz, rated power and 25°C ambient temperature if not mentioned specifically.
- #2: Ripple noise is measured with 0.1uF MLCC & 10uF low ESR capacitor.
- #3: Calculated by Telcordia SR332 at 25°C ambient temperature.
- #4: When operating altitude is higher than 2000m, the environment temperature derating factor is 0.36°C/100m.
- #5: Hold up time will be evaluated at 80% of rated load.

Mechanical Specification

(Cable assignment may be varied by request)

