

650W Multiple Output 80+Bronze Efficiency Data Sheet

LITEON

This is a high efficiency and high power factor (PF), multiple-output AC to DC switching mode power supply unit which can provide up to 650 watts continuous with forced cooling by a smart FSC (fan speed control) circuitry. There is a built-in auxiliary converter (5VSB) for energy saving purpose. It complies with 80+brone as well as worldwide safety and EMC regulations (refer to details below). It is suitable for various consumer, commercial and gaming PC applications.

-



Model Name	PS-8651-2						
Output							
Rated power	650W						
Rated voltage	12V1	12V2	12V3	12V4	5V	3.3V	5Vsb
Rated current	14.5A	18.5A	15A	15A	15A	8A	4A
Ripple & Noise(max.) (note #2)	120mV	120mV	120mV	120mV	50mV	50mV	50mV
Line & load regulation	±5%	±5%	±5%	±5%	±5%	±5%	±5%
Hold-up time(min.) (note #5)	16ms						
Timing: AC ON delay / rising (max.)	2 sec / 20ms						
Input							
Rated voltage range	100~240Vac						
Operated voltage range	90~264Vac, 300Vac for 5 sec						

Current range (max.)	8A/100Vac
Power factor (typ.)	>0.99/115Vac; >0.95/230Vac
Inrush current (typ.)	No component damaged ($<I^2 \cdot t$)
Frequency range	50-60Hz
Leakage current (max.)	1.0mA at 240Vac
Efficiency (min.)	87% - 90% - 87% (at 20% - 50% - 100% of rated load)
Standby power saving (min.)	Pin<1.0W at 5Vsb/0.1A, Pin<0.5W at 5Vsb/0.05A (at REM_OFF)
Protection Function	
Over voltage (max.)	145% of rated voltage, latch-off protection for +12V/+5V/+3.3V
Over current (max.)	<60A for +12V, <240VA for +5V/+3.3V <8A, hiccup protection for +5Vsb
Short circuit at O/P	No damage, latch-off protection for +12V/+5V/+3.3V No damage, hiccup protection for +5Vsb
Over temperature	No damage, latch-off protection
Others	
MTBF (min.) (note#3)	700K hours @ rated load
Environment	
Temperature	(operating) 0~50°C / (storage) -40~85°C
Humidity	(operating) 10~90% RH non-condensing / (storage) 5~95% RH
Altitude (max.)	5000 meters
Mechanical	
Dimension	150.0(L)*140.0(W)*86.0mm(H)
Vibration	10~500 Hz, 5G 20min./1cycle per axis for all axes (X, Y, Z)
Weight (typ.)	1.5kg
Safety	
Standard	IEC/EN 60950-1, K60950-1, IEC/EN 62368-1, CNS14336-1
Withstand voltage	Input-Output: 4242VDC / Input-FG: 2150VDC
Isolation resistance(min.)	Input-Output: 100Mohm @ 500VDC, 25°C, 70%RH
EMC	
EN55032 (CISPR32)	Conducted EMI: class B / Radiated EMI: class B
FCC	Conducted EMI: class B / Radiated EMI: class B
EN61000-3-2	Harmonic distortion: class D
EN61000-4-2	ESD: ±8KV contact discharge / ±15KV contact discharge
EN61000-4-3	Radiated RF immunity: 3V/m
EN61000-4-4	EFT: ±1KV (AC port)
EN61000-4-5	Surge: ±1KV DM / ±2KV CM
EN61000-4-6	Conducted RF immunity: 3V/m

EN61000-4-8	Magnetic field immunity: 3A/m
EN61000-4-11	Voltage dip immunity

Notes

- #1: All specification defined at 230Vac/50Hz, rated power and 25°C ambient temperature if not mentioned specifically.
- #2: Ripple noise is measured with 0.47uF MLCC & 47uF low ESR capacitor.
- #3: Calculated by Telcordia SR332 at 25°C ambient temperature.
- #4: When operating altitude is higher than 2000m, the environment temperature derating factor is 0.36°C/100m.
- #5: Hold up time will be evaluated at 80% of rated load.

Mechanical Specification

